

CEDRIA Priming Plus

Technical Sheet

Treatments Range

Product Description

Preventative and restorative protector. Water-based. Designed for the treatment of wood. WATER-BASED WOODWORM KILLER.

Properties

- Preventative-restorative against fungi and xylophagous insects.
- Odourless
- Rapid drying.
- Ready to use. Easy application.
- Neutral. Does not alter the colour of the wood.

Recommended Uses

For all types of wood, furniture, art objects, beams, dado rails, mouldings, skirting boards... which need protecting. Exterior – Interior.

Technical Characteristics

Odour	Odourless
Viscosity	10" - 16" CF4
Density (20°C)	1.00 kg/l
Solvent Type	Water
Drying	Touch dry: 1-2 hours. Repainted: 12 hours
Application Conditions	Maximum Relative Humidity 65%. Temperature between 5° and 35°
Storage	Conserve inside at temperatures between 5°C and 35°C
Container sizes	1l, 5l and 20l
Utensils and Cleaning	Brush, spray-gun (Only indoors). Clean with water
Coverage	4-6 m ² /l (preventative) and 3-4 m ² /l (restorative) depending on state of surface and wood type
BPR Registration number	ES/MRF(NA)-2019-08-00630-4-1 (Profesional use) // ES/MRF(NA)-2019-08-00630-5-1 (General public use)

PROFESSIONAL USE: CEDRIA PRIMER/Imprimación Tratante Plus Pro: Containers greater than 2,5 liters.

GENERAL PUBLIC USE: CEDRIA PRIMER/Imprimación Tratante Plus: Containers UP to 2,5 liters

Safety

- All current legislation must be followed in the case of storage and handling.
- Storage Life: 2 years in sealed containers and at storage conditions as recommended in the Technical Characteristics section.
- Prevent the product or product residues coming into contact with water courses. Remember: the care and protection of the environment is the legacy for our future generations.
- Keep out of the reach of children.

Quality Guarantee

CEDRIA products have been developed, manufactured and sold under the most rigorous quality standards. These recommendations are made in accordance with the current state of our knowledge and provide general information about the application and use of the products. Given the variety of substrates, uses and application techniques, the purchaser/user remains responsible for checking the materials, their application and the final result. For this reason, the purchaser/user is advised to test the product prior to the final application.

Application and Preparation of the wood

It is essential to prepare the wood properly before applying the product:

1. The wood should be dry (with less than 18-20% humidity).
2. The wood should be free from dust, grease, residues and other substances.
3. Product is ready to use.
4. Stir (do not shake) the product with a spatula before using.

New Wood

- **It is essential to prepare the wood before applying the product. See the section on application and preparation of wood.**
- Apply CEDRIA PRIMING PLUS by brush or spray-gun, particularly at the ends of the wood. PREVENTATIVE USAGE 200g/m². Outdoors do not apply by spraying.
- Wait 12 hours before applying the chosen finish.

Previously painted or varnished wood

- **It is essential to prepare the wood before applying the product. See the section on Application and Preparation of wood.**
- Before applying CEDRIA PRIMING PLUS it is essential to remove previous finishes by sanding the wood in the direction of the grain or stripping the wood with CEDRIA REMOVER GEL*¹.
- Apply CEDRIA PRIMING PLUS with a brush, spray-gun or by injection into drill holes. RESTORATIVE USAGE 300 g/m². Outdoors do not apply by spraying.
- Wait 12 hours before applying the chosen finish.

IMPORTANT: If you do not remove the remains of the previous product, apply CEDRIA PRIMING PLUS by injection into drill holes to aid penetration of the product into the wood. RESTORATIVE USAGE 300 g/m².

Additional Recommendations

- Drying times will vary according to temperature and relative humidity.
- The performance and behaviour of the product may vary depending on the type of wood.

*1: See the Technical Sheet for the product.