

Treatments Range

Product Description

Wood putty designed for filling cracks, holes and general imperfections. Water-based.

Properties

- Repairs imperfections in the wood caused by woodworm.
- Easy application.
- Rapid drying.
- Environmentally friendly.

Recommended Uses

For doors, frames, parquet floors and other general wooden items. Exterior – Interior.

Technical Characteristics

Odour	Low odour
Viscosity	> 250000
Density (20°C)	1.90-2.00 g/cm ³
Solvent Type	Water
Drying	1 hour
Application Conditions	Maximum Relative Humidity 65%. Temperature between 5° and 35°
Storage	Conserve inside at temperatures between 5°C and 35°C
Container sizes	350 g
Utensils and Cleaning	Spatula. Clean with water immediately after use.
Colours	White, Pine/Beech, Oak, Sapele and Walnut
Coverage	1 kg/m ²

Safety

- All current legislation must be followed in the case of storage and handling.
- Storage Life: 1 year in sealed containers and at storage conditions as recommended in the Technical Characteristics section.
- Prevent the product or product residues coming into contact with water courses. Remember: the care and protection of the environment is the legacy for our future generations.
- Keep out of the reach of children.

Quality Guarantee

CEDRIA products have been developed, manufactured and sold under the most rigorous quality standards. These recommendations are made in accordance with the current state of our knowledge and provide general information about the application and use of the products. Given the variety of substrates, uses and application techniques, the purchaser/user remains responsible for checking the materials, their application and the final result. For this reason, the purchaser/user is advised to test the product prior to the final application.

CEDRIA Masillas

Preparation of the surface

It is essential to prepare the wood properly before applying the putty:

1. The surface must be dry.
2. The surface must be free from grease, residues and other substances. Before applying the putty it is advisable to brush the surface being treated to remove any dust and particles.
3. Product is ready to use.

Application

- **It is essential to prepare the surface before applying the putty. See the section on the Application and Preparation of the surface.**
- Knead the putty in your fingers
- With the help of a spatula, fill the surface of the wood with CEDRIA MASILLAS.
- Leave to dry. The drying time will depend on the depth of the filling and the environmental conditions.
- Once dry, sand the repaired area with P180 sandpaper to obtain the desired finish and afterwards apply the desired product (wood stain, paint, varnish...)

Additional Recommendations

- Drying times will vary according to temperature and relative humidity.
- Do not use in areas that are permanently wet.
- CEDRIA MASILLAS is compatible with previous or subsequent applications of most water-based wood stains and varnishes. For other types of treatment, test before applying.
- Before filling holes in the wood caused by xylophagous insects, it is recommended to use CEDRIA MATACARCOMA*1 or CEDRIA IMPRIMACIÓN TRATANTE*1.

*1: See the Technical Sheet for the product.