

Primer Range

Product Description

Sealer for preparing interior wood before varnishing. Offers total transparency and improves the finish of the varnish.

Properties

- Seals pores and regulates the absorption of the surface.
- Great filling ability.
- Easily sanded.
- Compatible with all types of varnish.
- Does not alter the colour of the wood.
- Rapid drying. Odourless
- Environmentally friendly.

Recommended Uses

Suitable for sealing surfaces of carpentry and do-it-yourself projects. Ideal for the varnishing of parquet flooring. Interior.

Technical Characteristics

Resin	Fine particle acrylic
Finish	Matt
Odour	Odourless
Viscosity	Brookfield 2000 – 3000 mPa.s (L3, 50 25°C)
Density (20°C)	1.05 kg/l
Solvent Type	Water
VOC	Contains 30g/l. - Limit value 2004/42/CE-IIA cat. g) is VOC max. 30. g/l (2010).
Drying	30 minutes
Application Conditions	Maximum Relative Humidity 65%. Temperature between 5° and 35°
Storage	Conserve inside at temperatures between 5°C and 35°C
Container sizes	750ml and 4l
Utensils and Cleaning	Brush or spray-gun. Clean with water
Colours	Neutral
Coverage	8-10m ² /l depending on state of surface and wood type

Safety

- All current legislation must be followed in the case of storage and handling.
- Storage Life: 2 years in sealed containers and at storage conditions as recommended in the Technical Characteristics section.
- Prevent the product or product residues coming into contact with water courses. Remember: the care and protection of the environment is the legacy for our future generations.
- Keep out of the reach of children.

Quality Guarantee

CEDRIA products have been developed, manufactured and sold under the most rigorous quality standards. These recommendations are made in accordance with the current state of our knowledge and provide general information about the application and use of the products. Given the variety of substrates, uses and application techniques, the purchaser/user remains responsible for checking the materials, their application and the final result. For this reason, the purchaser/user is advised to test the product prior to the final application.

Application and Preparation of the wood

It is essential to prepare the wood properly before applying the product:

1. The wood should be dry (with less than 18-20% humidity).
2. The wood should be free from dust, grease, residues and other substances.
3. Product is ready to use (Only when using a spray-gun, if necessary, dilute with 5% water, preferably distilled).
4. Stir (do not shake) the product vigorously with a spatula before using.

New Wood

- **It is essential to prepare the wood properly before applying the product. See the section on application and preparation of wood.**
- Apply 1 coat of CEDRIA TAPAPOROS. After about 3 hours, sand the surface on which the coat was applied. If the surface still has uneven areas, apply a second coat. Drying time between coats 1 hour.
- Clean the surface of dust from the sanding and then apply the chosen varnish.

Wood that is worn or in a poor state

- **It is essential to prepare the wood properly before applying the product. See the section on application and preparation of wood.**
- Remove traces of previous products by sanding the wood in the direction of the grain or by stripping it with CEDRIA DECAPANTE*1.
- Apply 1 coat of CEDRIA TAPAPOROS. After about 3 hours, sand the surface on which the coat was applied. If the surface still has uneven areas, apply a second coat. Drying time between coats 1 hour.
- Clean the surface of dust from the sanding and then apply the chosen varnish.

Additional Recommendations

- For woods such as Oregon or Longleaf Pine which are resinous or have resinous knots, after sanding and before applying the product, it is recommended to wipe the wood thoroughly with a cloth impregnated with CEDRIA WOOD NET*1.
- CEDRIA TAPAPOROS is compatible with previous or subsequent applications of most water-based wood stains and varnishes. For greater security, it is recommended to test the product, as is the case with other types of repainting.
- Drying times will vary according to temperature and relative humidity.
- The performance and behaviour of the product may vary depending on the type of wood.
- When sanding avoid using metallic scouring pads, steel wool or any other tool that can leave metal remnants.

*1: See the Technical Sheet for the product.